



Kitter Corporation

Material Safety Data Sheet

24-7 Fast Drying High Gloss Floor Finish

Section 1: Identification

Product Name: 24-7 Fast Drying High Gloss Floor Finish
Manufacturer's Name: Kitter Corporation
Address: 100 S. Cleveland (P.O. Box 9680) Amarillo, Texas 79105
Emergency Phone Number: Chem-Tel 1-800-255-3924
Product Stewardship: 806-376-1448
Date Prepared: April 18, 2003

Section 2: Composition / Information on Ingredients

CHEMICAL	C.A.S. NUMBER	WEIGHT %	
Water	7732-18-5	65 - 99	
2-(2-ethoxyethoxy) ethanol	111-90-0	1 - 5	
Dipropylene Glycol Methyl Ether	34590-94-8	1 - 5	
Polyolefin Emulsion	N/A	1 - 5	
Styrene Acrylic Emulsion	N/A	1 - 10	
Polyethylene Polymer	N/A	1 - 5	
OSHA Hazardous Components (29 CFR 1910.1200):			
	OSHA PEL	ACGIH TLV	Supplier
2-(2-ethoxyethoxy) ethanol	100 ppm	100 ppm	N/A
Dipropylene Glycol Methyl Ether	100 ppm	100 ppm	N/A

Section 3: Hazard Identification

Potential Health Effects:

Eyes: Contact with eyes may cause irritation
Skin: Prolonged or repeated contact with skin may cause irritation.
Ingestion: Swallowing may cause abdominal discomfort, nausea, vomiting and diarrhea.
Inhalation: Not a likely route of exposure.
Medical Conditions Aggravated by Overexposure: Repeated skin contact may cause dermatitis.

Section 4: First Aid Measures

Eye Contact: Immediately flush eyes with water for at least 15 minutes. Seek medical attention if symptoms persist.
Skin Contact: Wash skin with water and remove contaminated clothing. Wash contaminated clothing before reuse.
Ingestion: Do not induce vomiting. If conscious and alert, give two glasses of water. Seek medical attention immediately.
Inhalation: Remove to fresh air. Seek medical attention if symptoms persist.

Section 5: Fire Fighting Measures

Flash Point & Method: None, PMCC
Flammable Limits: LEL - N/A UEL - N/A
Auto ignition Temperature: N/E
General Hazard: None
Fire Fighting Instructions: Use self-contained breathing apparatus for maximum respiratory protection. Use water spray to cool containers in area.
Unusual Fire & Explosion Hazards: None known

Section 6: Accidental Release Measures

Small Spills: Soak up with absorbent. Shovel in waste containers. Flush area with water.
Large Spills: Recover spilled material for reprocessing or disposal. See Section 13 for proper disposal information.

Section 7: Handling & Storage

Storage Temperature: Ambient
Storage Pressure: Atmospheric
General: Keep container closed when not in use. Store in a cool, well-ventilated area. Avoid overheating or freezing. Wash thoroughly after handling. Keep out of reach of children. Spilled material is slippery.