



Kitter Corporation

Material Safety Data Sheet

SILVER SOAK Powdered Flatware Brightener

Section 1: Identification

Product Name: SILVER SOAK Powdered Flatware Brightener
Manufacturer's Name: Kitter Corporation
Address: 100 S. Cleveland (P.O. Box 9680) Amarillo, Texas 79105
Emergency Phone Number: Chem-Tel 1-800-255-3924
Product Stewardship: 806-376-1448
Date Prepared: June 16, 2003

Section 2: Composition / Information on Ingredients

CHEMICAL	C.A.S. NUMBER	WEIGHT %
Sodium Carbonate Anhydrous	497-19-8	40 - 60
Trisodium Phosphate	10101-89-0	20 - 40
Sodium dodecylbenzene sulfonate	25155-30-0	1 - 5

OSHA Hazardous Components (29 CFR 1910.1200):

	OSHA PEL	ACGIH TLV
Sodium Carbonate Anhydrous	N/E	N/E
Trisodium Phosphate	N/E	N/E
Sodium dodecylbenzene sulfonate	N/E	N/E

Section 3: Hazard Identification

Potential Health Effects:

Eyes: Contact with eyes causes severe eye injury.
Skin: Product may cause severe skin irritation. Prolonged or repeated exposure may cause dermatitis.
Ingestion: Harmful if swallowed. Swallowing may cause severe irritation of mouth and throat.
Inhalation: Dust may be irritating to the nose, throat and respiratory tract.
Medical Conditions Aggravated by Overexposure: Repeated skin contact may cause dermatitis.

Section 4: First Aid Measures

Eye Contact: Immediately flush eyes with water for at least 15 minutes. Seek medical attention.
Skin Contact: Wash skin with water and remove contaminated clothing. Wash contaminated clothing before reuse.
Ingestion: DO NOT induce vomiting. If conscious and alert, give two glasses of water. Seek medical attention immediately.
Inhalation: Remove to fresh air. Seek medical attention if symptoms persist.

Section 5: Fire Fighting Measures

Flash Point & Method: N/A
Flammable Limits: LEL - N/A UEL - N/A
Auto ignition Temperature: Not Determined
General Hazard: None
Fire Fighting Instructions: Use self-contained breathing apparatus for maximum respiratory protection. Use water spray to cool containers in area.
Unusual Fire & Explosion Hazards: None known

Section 6: Accidental Release Measures

Small Spills: Shovel in waste containers.
Large Spills: Recover spilled material for reprocessing or disposal. See Section 13 for proper disposal information.

Section 7: Handling & Storage

Storage Temperature: Ambient
Storage Pressure: Atmospheric
General: Keep container closed when not in use. Store in a cool, well-ventilated area. Avoid overheating or freezing. Wash thoroughly after handling. Keep out of reach of children.

SILVER SOAK Powdered Flatware Brightener

Section 8: Exposure Control / Personal Protection

Engineering Controls: Local exhaust ventilation is acceptable. Mechanical ventilation is recommended.

Personal Protection:

Respiratory Protection: If vapors, fumes or dusts are present use a MSHA or NIOSH approved respirator, a fresh air breathing apparatus or a self-contained breathing apparatus.

Hand Protection: Chemical resistant gloves.

Eye Protection: Safety glasses or goggles.

Other Recommendations: Not required.

Section 9: Physical & Chemical Properties

Specific Gravity (H ₂ O=1)	1.205	Boiling Point	>200°F
Vapor Pressure (mmHg.)	N/A	Melting Point	>34°C
Vapor Density (AIR=1)	>1	Solubility in Water	20%
Evaporation Rate (n-BuAc=1)	<1	pH	N/A

Appearance and Odor: Green powder with a citrus odor.

Section 10: Stability & Reactivity

General: Stable, hazardous polymerization will not occur.

Incompatible Materials: Reactive alkali metals, strong acids and bases.

Hazardous Decomposition: Forced combustion yields carbon oxides.

Section 11: Toxicological Information

Results of Component Toxicity Tests Performed:

For Sodium Carbonate Anhydrous (497-19-8): Oral LD₅₀ = 4100 mg/kg (Rat)

For Trisodium Phosphate (10101-89-0): Oral LD₅₀ = 7400 mg/kg (Rat)

For Sodium dodecylbenzene sulfonate (25155-30-0): Oral LD₅₀ = 1260 mg/kg (Rat)

No Chemicals used in this product are listed as carcinogens or suspected carcinogens by the National Toxicological Program, IARC monographs or OSHA.

Section 12: Ecological Information

Aquatic Effects: 96-hour Rainbow Trout LC₅₀ >100 mg/L
48-hour "Daphnia magna" EC₅₀ >100 mg/L

Section 13: Disposal Considerations

Waste Disposal Method: Recover liquid or dispose waste material in accordance with all applicable federal, state and local regulations and laws. Material collected with absorbent may be disposed of in a permitted landfill.

RCRA 40 CFR 261 Classification: Unused material is not regulated.

Section 14: Transportation Information

U.S. DOT Information: This material is not regulated by the U.S. Department of Transportation.

Proper Shipping Name: N/A

Hazard Class: N/A

Packing Group: N/A

UN Number: N/A

Limitations: N/A

Section 15: Regulatory Information

U.S. Federal Regulations: MSDS complies with OSHA's Hazard Communication Rule, 29CFR1910.1200.

CERCLA / Superfund, 40 CFR 117: N/A

SARA Superfund and Reauthorization Act of 1986 Title III Sections 302, 311, 312 and 313:

Section 302: None of the chemicals are listed in Section 302

Section 311 / 312: By our hazard evaluation, this product is hazardous.

EPA Hazard: Immediate (acute) health hazard

Section 313: None of the chemicals are listed in Section 313.

TSCA: All substances are TSCA Listed.

Section 16: Other Information

Revision Dates, Sections, Revised By: 06-16-2003, CREATED, D. Sloan

Abbreviations used in this Document: N/A – Not Applicable, N/E – Not Established

Disclaimer of Liability: The information contained herein is, to the best of our knowledge, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.